

MATERIAL SAFETY DATA SHEET

May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.	HMIS HAZARD RATING												
TELLUS MEDICAL PRODUCTS 77-971 WILDCAT DR. SUITE C PALM DESERT, CA. 92211	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 33%;">HEALTH</td> <td style="width: 33%;">3</td> <td style="width: 33%;">0 = INSIGNIFICANT</td> <td style="width: 33%;">3 = HIGH</td> </tr> <tr> <td>FLAMMABILITY</td> <td>0</td> <td>1 = SLIGHT</td> <td>4 = EXTREME</td> </tr> <tr> <td>REACTIVITY</td> <td>0</td> <td>2 = MODERATE</td> <td></td> </tr> </table>	HEALTH	3	0 = INSIGNIFICANT	3 = HIGH	FLAMMABILITY	0	1 = SLIGHT	4 = EXTREME	REACTIVITY	0	2 = MODERATE	
HEALTH	3	0 = INSIGNIFICANT	3 = HIGH										
FLAMMABILITY	0	1 = SLIGHT	4 = EXTREME										
REACTIVITY	0	2 = MODERATE											
TRANSPORTATION INFORMATION													
PROPER SHIPPING NAME	Cleaner, Non-regulated, (Hydrogen Peroxide 3%)												
HAZARD CLASS / PKG. GRP.	Not applicable REF. Not applicable												
IDENTIFICATION NUMBER	Not applicable LABEL None Required Ground												

SECTION 1 - PRODUCT / COMPANY IDENTIFICATION

IDENTITY (AS USED ON LABEL AND LIST)	Page 1 of 2
Tellus Hydrogen Peroxide Spray	
MANUFACTURER'S NAME Safetec of America, Inc.	EMERGENCY TELEPHONE NUMBER (24 Hours) (800) 255-3924
ADDRESS (NUMBER, STREET, P.O. BOX) 887 Kensington Avenue @ William L. Gaiter Pkwy.	TELEPHONE NUMBER FOR INFORMATION (716) 895-1822
(CITY, STATE AND ZIP CODE) Buffalo, NY 14215	DATE PREPARED January 31, 2006 SUPERSEDES NA

SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

HAZARDOUS COMPONENTS (SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))	CAS #	% (wt.) (OPTIONAL)	ACGIH TLV/TWA/STEL	
			PPM	MG/M ³
Hydrogen Peroxide	7722-84-1	2-4	1 (TLV/TWA)	1.5 (TLV/TWA)

This product is not known to contain a substance subject to Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR 372 at or above minimal amounts.

SECTION 3 - HEALTH HAZARD DATA

ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE	EMERGENCY AND FIRST AID PROCEDURES
INHALATION: May cause irritation of respiratory tract, characterized by coughing, choking or shortness of breath.	Remove victim to fresh air; provide oxygen if breathing is difficult; get medical attention.
EYES: Produces irritation, characterized by a burning sensation, redness, tearing, inflammation, and possible corneal injury. Vapors may cause eye irritation.	Immediately flush eyes with clear running water for a minimum of 15 minutes while holding eyelids open; get medical attention.
INGESTION: May cause irritation of the digestive tract. May lead to distention of the esophagus and stomach.	DO NOT induce vomiting. If victim is conscious and alert, give 2-4 cupfuls of milk or water. Never give anything by mouth to an unconscious person. Seek medical attention.
SKIN: May cause irritation. May cause skin discoloration. May cause reddening of the skin.	Wash contaminated skin with water; if irritation occurs and persists, seek medical attention.

HEALTH HAZARDS (ACUTE AND CHRONIC): Acute: May produce tissue damage to mucous membranes. Chronic: Repeated or prolonged exposure may produce lung or mucous membrane damage. Repeated or prolonged spray mist may produce chronic eye irritation, severe skin irritation, respiratory tract irritation leading to frequent attacks of bronchial infection

CARCINOGENICITY	NTP?	No	IARC MONOGRAPHS?	No	OSHA REGULATED?	No
-----------------	------	----	------------------	----	-----------------	----

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Preexisting skin, eye, or respiratory disorders may become aggravated through prolonged exposure.

MATERIAL SAFETY DATA SHEET

IDENTITY (AS USED ON LABEL AND LIST)

Tellus Hydrogen Peroxide Spray

Page 2 of 2

Date: January 31, 2006

SECTION 4 - FIRE FIGHTING MEASURES

FLASH POINT (METHOD USED) Not applicable	FLAMMABLE LIMITS (% Volume in Air for Lowest Flashing Component) Isopropyl Alcohol	LEL: Not applicable	UEL: Not applicable
---	---	---------------------	---------------------

EXTINGUISHING MEDIA

Use extinguishing media appropriate for the surrounding fire. Use flooding quantities of water.

SPECIAL FIRE FIGHTING PROCEDURES

Positive pressure NIOSH approved self-contained breathing apparatus (General Precaution).

UNUSUAL FIRE AND EXPLOSIVE HAZARDS

Slightly explosive to explosive in presence of shock, of acids or of alkalis..

SECTION 5 - PRECAUTIONS FOR SAFE HANDLING AND USE / LEAK PROCEDURES**STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED**

Spills should be collected with approved inert absorbent for disposal. Use suitable disposal containers.

WASTE DISPOSAL METHODS

Dispose of in accordance with Local, State, and Federal regulations. Products classified as non-hazardous may become hazardous waste upon contact with other products. Refer to "40 CFR Protection of Environment Parts 260-299" for complete waste disposal regulations. Consult your Local, State, or Federal Environmental Protection Agency before disposing of any chemicals.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Corrosive materials should be stored separately. Keep this and other chemicals out of reach of children.

SECTION 6 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION Ordinarily, none required	VENTILATION LOCAL EXHAUST: Recommended MECHANICAL (GENERAL): Not required
PROTECTIVE GLOVES Recommended	EYE PROTECTION Safety glasses
OTHER PROTECTIVE CLOTHING OR EQUIPMENT Eye wash stations should be nearby and ready for use.	WORK / HYGIENIC PRACTICES Practice safe work habits. Use according to label instructions.

SECTION 7 - PHYSICAL / CHEMICAL PROPERTIES

BOILING POINT 101°C (214 °F)	SPECIFIC GRAVITY (WATER=1) 1.009
VAPOR PRESSURE (mm Hg) No data	MELTING POINT 0.04°C (32.1 °F)
VAPOR DENSITY (AIR=1) No data	PH (1% solution in water) Neutral
SOLUBILITY IN WATER Soluble	EVAPORATION RATE (IPA=1) No data
APPEARANCE AND ODOR Clear, Colorless Liquid	% VOLATILES (BY VOLUME) No data

SECTION 8 - STABILITY AND REACTIVITY

STABILITY UNSTABLE: STABLE: XXX	CONDITIONS TO AVOID Light, sources of ignition, heat, metals, reducing agents
INCOMPATIBILITIES (MATERIALS TO AVOID) Oxidizers, slightly reactive with combustible materials, metals	
HAZARDOUS DECOMPOSITION OR BYPRODUCTS Thermal decomposition may emit nitrogen oxides, hydrogen, oxygen, hydrazoic acid.	
HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: XXX	CONDITIONS TO AVOID Temperatures above 300°C, alkaline materials.

The information contained herein is believed to be accurate but is not warranted to be so. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed.